



PEDESTRIAN OR LIGHT VEHICLE TRAFFIC
(SCALE 1:10)

NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.
2. BLOCKS SHALL BE LAID WITH A JOINT WIDTH OF 2 TO 5mm.
3. MODULAR PAVING AREAS CAN STILL ONLY BE TRAFFICKED AFTER FINAL FILLING OF JOINTS WITH CLEAN DRY SAND.
4. NO BLOCK CUT TO LESS THAN ONE QUARTER OF ITS ORIGINAL SIZE SHALL BE USED. CUTTING MAY BE CARRIED OUT USING A DIAMOND TIPPED WET BLADE SAW OR BLOCK SPITTED GUILLOTINE.
5. FOR SURFACE COATED BLOCK PAVING THE COLOUR COATING SHALL COMPLY WITH BS 6044 FOR PAVEMENT PAINT.
6. LAYING COURSE MATERIAL SHOULD BE CONSIST OF WELL-GRADED SAND, COMPLYING WITH THE GRADING ENVELOPE GIVEN IN BS 7533 PART 3, LAID 50MM THICK.
7. LAYING COURSE MATERIAL MAY BE SPREAD IN ONE LAYER, ALTERNATIVELY SAND MAY BE SPREAD IN TWO LAYERS. THE LOWER 2/3 BEING PRE-COMPACTED AND UPPER 1/3 UNCOMPACTED. AFTER COMPACTION REDUCTION WILL BE APPROX 15-20mm TO 50mm THICK 9-14mm TO 30mm THICK.
8. SUBBASE SHALL BE IN ACCORDANCE WITH CLAUSE 803 AS PER SPECIFICATION OF HIGHWAY WORKS.
9. COMPACTION SHALL BE UNDERTAKEN WITH A PLATE VIBRATOR, CONFORMING TO THE REQUIREMENTS OF ANNEX F BS 7533 PART 3.



COUNTY HALL
Pegs Lane
Hertford, Herts
SG13 8DN
Phone: 01992 555555

Revisions

- A - FEB 20 REVISED DETAIL
- B -
- C -

Drawing Title

PAVED AREAS
400 x 400mm MODULAR PAVERS

Dwg No: HST/1100/015

Scale at A4 : 1:10

Drawn	Approved	Revised
YS	HH	A
Checked	Date	Date
KK	JULY 11	FEB 20