



- NOTES:**
1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.
 2. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH HST/1100/002.
 3. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH HST/1100/043.
 4. FOR PRECAST CONCRETE FLAGS SIZES AND TYPE OF BOND DIMENSIONS REFER TO THE WORKS ORDER.
 5. PRECAST CONCRETE FLAGS SHALL BE LAID IN ACCORDANCE WITH THE RECOMMENDATIONS OF BS 7533 PART 4.
 6. ALL THE TACTILE SURFACE PATTERN PAVING SLABS SHALL BE PRECAST CONCRETE 400x400x50mm THICK, OR 450x450x65mm THICK.
 7. TACTILE PAVING SHALL BE EITHER BUFF OR RED COLOURED.
 8. MORTAR SHALL BE DESIGNATION (ii) OR (iii), CLAUSE 2404 AS PER SPECIFICATION OF HIGHWAY WORKS.
 9. ALL MORTAR POINTING SHALL BE COLOUR MATCHED TO THE FLAG.
 10. MORTAR PIGMENT SHALL COMPLY WITH BS EN 12878.
 11. SUBBASE SHALL BE ONE OF THE MATERIALS COMPLYING WITH CLAUSE 803 OR CLAUSE 891AR, 892AR, 893AR OR 894AR, AS SPECIFIED IN THE WORKS INFORMATION.
 12. WHEN EXCAVATING TO FOOTWAY FORMATION LEVEL, THE FULL DEPTH OF EXISTING MATERIAL, INCLUDING TOPSOIL SHALL BE REMOVED, ANY ADDITIONAL DEPTH OF EXCAVATION RESULTING FROM THIS SHALL BE BACKFILLED WITH SUB-BASE AS NOTE 9.



COUNTY HALL
 Pegs Lane
 Hertford, Herts
 SG13 8DN
 Phone: 01992 555555

Revisions

A -	FEB 20	REVISED DETAIL
B -		
C -		

Drawing Title

FOOTWAY TYPE 6
 PRECAST CONCRETE TACTILE
 FOOTWAY

Dwg No: HST/1100/027		
Scale at A4 : 1:10		
Drawn	Approved	Revised
YS	HH	A
Checked	Date	Date
KK	JULY 11	FEB 20