



- NOTES:**
1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.
  2. PRE-CAST OR IN-SITU UNITS AS STATED IN THE WORKS ORDER.
  3. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH DWG NUM HST/1100/002.
  4. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH DWG NUM HST/1100/043.
  5. LAYING COURSE MATERIAL SHOULD BE CONSIST OF WELL-GRADED SAND, COMPLYING WITH THE GRADING ENVELOPE GIVEN IN BS 7533 PART 3, LAID 50mm THICK.
  6. COMPACTION SHALL BE UNDERTAKEN WITH A PLATE VIBRATOR, CONFORMING TO THE REQUIREMENTS OF ANNEX F BS 7533 PART 3.
  7. SUBBASE SHALL BE INCREASED TO 150mm THICK IF AREA IS USED BY LIGHT TRAFFIC.
  8. SUBBASE SHALL BE ONE OF THE MATERIALS COMPLYING WITH CLAUSE 803 OR CLAUSE 891AR, 892AR, 893AR OR 894AR, AS SPECIFIED IN THE WORKS INFORMATION.
  9. WHEN EXCAVATING TO FOOTWAY FORMATION LEVEL, THE FULL DEPTH OF EXISTING MATERIAL, INCLUDING TOPSOIL SHALL BE REMOVED, ANY ADDITIONAL DEPTH OF EXCAVATION RESULTING FROM THIS SHALL BE BACKFILLED WITH SUB-BASE AS NOTE 8.



COUNTY HALL  
 Pegs Lane  
 Hertford, Herts  
 SG13 8DN  
 Phone: 01992 555555

Revisions

A -	FEB 20	REVISED DETAIL
B -		
C -		

Drawing Title

**FOOTWAY TYPE 8  
 GRASS/CONCRETE PAVING**

Dwg No: <b>HST/1100/029</b>		
Scale at A4 : 1:10		
Drawn YS	Approved HH	Revised A
Checked KK	Date JULY 11	Date FEB 20